<u>Technical information</u> Silent Pro Luxury Insulation Layer

Art. no. 405 325

Product

Product

polyurethane binder, single sided with non-woven lining. composition **Advantages** - The premium product for use under floating hard surface floor coverings - Excellent values for footfall and impact sound reduction through high self-weight and unique formulation - "Forest floor effect" reduces impact to joints and spine Technical data Material thickness: approx. 3 mm (+/- 0.15 mm) **DIN CEN/TS 16354** Weight per unit area: approx. 2.8 kg/m² (+/- 0.15 kg/m²) Weight: 1000 kg/ m³ (roll-out cork underlay approx. 200 kg/ m³) Thermal resistance approx. 0.01 m² K/W **DIN CEN/TS 16354** Suitable under parquet and laminate floor Underfloor heating: Footfall sound improvement: up to 19 dB (+/- 2 dB) **DIN EN 10140** Room sound improvement: 29% (+/- 2 %) When walking on the floor a more pleasant sound is produced because of the **EPLF Norm WD 021029-5** Resistance to constant pressure: approx. 15 t/m² (~150 kPa) **DIN CEN/TS 16354 Dimensions:** 5,27 m x 0,95 m **DIN CEN/TS 16354** Roll coverage: 5.0 m² Pallet content: 200 m² (40 rolls) Packaging: individual rolls wrapped in foil with guide lines 40 rolls comprise the display on a Euro pallet

Acoustic mat for floating installation under laminate and parquet

Permanently flexible underlay material made of mineral fillers (mostly siliceous sand) and

Environment

- TÜV tested for harmful substances
- Recyclable (EWC no.: 170604)

Flammability class

without top covering:

- Can be disposed of in domestic rubbish

Free from softeners, asbestos, formaldehyde, cadmium, halogens and other heavy metals.

Efl (DIN EN 13501-1) no harm to health with fire

Silent Pro is produced CFC-free, and has neither solvents nor ozone-damaging substances.

Installation

- Use PE film as an underlayment on all mineral subfloors
- Install with non-woven fabric down
- Easy and dust-free to cut to size with a general-purpose cutter (carpet knife)
- Fit the ends together tightly; do not overlap or leave gaps

This technical information is for your guidance and is based on our most up to date knowledge. It makes no representation or warranty, express or implied, as to any specific properties of the described product within the meaning of the statutory warranty regulations.